

# **DECIACAMP-S**

Version 1.1.0 - 2023

#### DESCRIPTION

DECIACAMP-S allows white lines to be drawn on turf without causing irritation as it is free of Calcium Hydroxide. Can be used with all markers on the market. Product designed to have characteristics of adherence to turf, high visibility, excellent whiteness and excellent coverage. Simply dilutable with water.

DECIACAMP-S is also available in Red, Blue, Green, Yellow and dark green.

## **PHYSICAL CHEMICAL CHARACTERISTICS**

COLOR ASPECT COMPOSITION SPECIFIC WEIGHT VISCOSITY DRY RESIDUAL white, red, blue, green, yellow and dark green. matte selected natural fillers  $1.50 \pm 0.05$  g/cm<sup>3</sup> at 20 °C  $10000 \pm 2000$  cps R6 rpm 60  $63 \pm 2\%$ 

Note: These properties are typical ones and are not to be considered specific. Marginal deviations of the values do not affect the efficacy or property of the product.

# **APPLICATION CHARACTERISTICS**

TEMP. APPLICATION.	between +5 and +35 degrees °C
DRYING	Approx. 15 to 20 minutes (reported at 20°C and 65% R.H.)
DILUTION	300-400% V/V with potable water
EQUIPMENT	airless
YIELD	3 It of product for a regulation soccer field of first tracking; for maintenance 2 It of product (variable value depending on the nozzles used in painting and
	the application speed)

**<u>APPLICATION SYSTEM</u>** Mix paint before use, dilute with water by mixing thoroughly, adjust equipment according to application requirement or according to turf condition.

#### SUPPORTS: turf

# PACKAGING

PACKAGING

plastic bucket It 10 - It 3

## **GENERAL NOTES.**

The product is sensitive to frost. It is recommended, to be stored at a temperature between +5° and +25°C. Stored in the original tightly closed packages, and undiluted with water, it has a long storage period.

All of the above technical information contained within this sheet is the result of careful laboratory tests and practical experience. They do not represent a legal warranty, expressed or implied, about the use of our product as used outside of our control. Each user should verify the effectiveness and behavior of our product with regard to its specific applications.